



Double-shot feature

No-adjust feed system
reduces down time

Needle spacing knob

Needle spacing range:
8mm – 12mm

25,000 staple-spool capacity
means less reloading

Ethernet port
RS232 port

Input AC 100-240
VAC 50/60 Hz, .50A
(power converter)

On/off switch

Adjustable stopper



User interface for
system
programmability

Light provides
excellent visibility

Safety guard

Fine needle for delicate fabrics

Adjustable needles

Range: 8mm

12mm

Fine Fabric Plastic Staple® Fasteners

Stock No.	Size	Color	Qty./Reel	Qty./Case
15001™	1/2" (13mm)	Clear	25,000	100,000
15002™	1/2" (13mm)	White	25,000	100,000
15003™	1/2" (13mm)	Black	25,000	100,000
15004™	1/2" (13mm)	Grey	25,000	100,000
15004™	1/2" (13mm)	Orange	25,000	100,000

Plastic Staple® Accessories

Stock No.	Description
15009™	Foot Pedal – Standard
10442™	Foot Pedal – Heavy Duty

Plastic Staple® Attachers

Stock No.	Model No.	Description
15000™	ST9500™	Input AC 100-240 VAC 50/60 Hz .50A

Fine Fabric Plastic Staple® Needles

Stock No.	Description	Qty./Kit
15010™	Fine Fabric	4
15011™	Ultra Fine Fabric	4