

TOLKAR MIRACLE Sample Dyeing Machines

40 - 100 - 200 - 300 - 400 - 500 - 600 lt

		Miracle GD 40	Miracle GD 100	Miracle GD 200	Miracle GD 300	Miracle GD 400	Miracle GD 500	Miracle GD 600
Drum Volume	(It)	40	100	208	300	400	500	600
Drum Diameter	(mm)	420	610	762	762	915	915	1.092
Drum Depth	(mm)	300	345	460	662	610	760	642
Motor Power	(kw)	1,5	1,5	3	4	5,5	7,5	11
Width	(mm)	715	825	990	990	1.180	1.180	1.460
Depth	(mm)	980	860	1.030	1.300	1.345	1.525	1.590
Height	(mm)	1.060	1.190	1.450	1.450	1.780	1.780	2.000
Weight	(kg)	280	350	595	770	1.125	1.230	2.250



1:2-1:3 LIQUOR RATIO dry garments



POLYRIB ECO DRUM SYSTEM

less water, chemicals, steam and waste water

%40 lessless dyes | electric energy





High speed dyeing with Spin Dye Jet Spraying Technology

Prevents all crease marks, abrassion and undesired mechanical effects.

Sustainable dyeing technology.



300 G

EXTRACTION

FORCE











TOLKAR ULTIMATE **CONTROL SYSTEM**

remote access enables updates of parameters or versions, recipe preparation, upload/download, recipe transfer to desired machines

USB programme and parameter transfer between machines 100 recipes, 100 steps


reporting amount of dyed garments, consumption of water, electric, steam, loading and operating times (Optional)

Controlled Touchscreen Control Panel

PLC

316 L **INNER DRUM**





Indirect Steam Heating Sample recipe ---> Bulk Recipe

Direct recipe transfer from sample to bulk machines without any correction.

DYE INLET

(1st 2nd and 3rd tank optional)

Steel Outer

Structure

Automatic precision in accordance with Automatic Weighing System (Optional)

Consumptions and productivity

(Optional)

Acquisition System

(Optional)